


See Standard 701400 for approach
Start of lane closure taper



DETAIL A

(BARRIER WALL REFLECTORS)

SYMBOLS

- Arrow board
- Work area
- Sign
- Direction indicator barricade with steady burn monodirectional light
- Type II barricade, drum, or vertical barricade with steady burn monodirectional light
- Temporary concrete barrier
- Type C Monodirectional reflector
- Vertical panel with steady burn monodirectional light.
- Impact attenuator

- ① ReflectORIZED temporary pavement marking tape shall be placed throughout the taper and along-side the work area. The edge line shall be white for right lane closure and yellow for left lane closures.
- ② Vertical panels at 7.6 m (25') centers with steady burning monodirectional lights.

GENERAL NOTES

This standard is used where at any time any vehicle, equipment, workers or their activities will encroach on the lane adjacent to the shoulder, or on the shoulder within 600 mm (24") of the edge of pavement for day light operation exceeding one day and where temporary concrete barrier is utilized.

This Standard must always be used in combination with Standard 701400.

This standard also applies when work is being performed in the left lane. Under these conditions, the set up would be a mirror image to what is shown.

All dimensions are in millimeters (inches) unless otherwise shown.

DATE	REVISIONS
4-15-04	Revised signs and notes.
4-1-04	Revised to provide consistency on freeway/expressway closures.

**LANE CLOSURE,
FREEWAY/EXPRESSWAY,
WITH BARRIER**

STANDARD 701402-05

Illinois Department of Transportation

APPROVED April 15, 2004

ENGINEER OF OPERATIONS *[Signature]*

APPROVED April 15, 2004

ENGINEER OF DESIGN AND ENVIRONMENT *[Signature]*

ISSUED 1-1-00